



# NACHI BEARINGS OF AMERICA CORP.



## TIMKEN E-TTU-TRB-3 15/16 Take Up Unit Bearings

Bearing No. E-TTU-TRB-3 15/16

E-TTU-TRB-3 15/16 Bearing 2D drawings and 3D CAD models

Category	Take Up Unit Bearings
Inventory	0.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	31.87
EAN	0053893778761
Product Group	M06288
Component Description	Take Up Bearing Only
Rolling Element	Tapered Roller Bearing
Housing Style	Unit Only - Half Round Top Angle
Mounting Method	Concentric Collar
Compatible Take Up Frame	Not Specified
Adjustment Travel Length	0
Housing Material	Cast Iron
Other Features	Double Row   Double Collar   Two Lip Seal   Electrodeposition Coating   With Set Screw
Inch - Metric	Inch
Long Description	Take Up Bearing Only; 3-15/16" Bore; Tapered Roller Bearing; Unit Only - Half Round Top Angle; Concentric Collar Mount; Cast Iron Housing Material
Category	Take Up Units
UNSPSC	31171533



## NACHI BEARINGS OF AMERICA CORP.

Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Take Up
Manufacturer URL	<a href="http://www.timken.com">http://www.timken.com</a>
Manufacturer Item Number	E-TTU-TRB-3 15/16
Weight / LBS	70.19
d	3.938 Inch   100.025 Millimeter
Slot Width	0 Inch   0 Millimeter
Slot to Slot Distance	0 Inch   0 Millimeter
Shaft Size	3.9375 in
Shaft Size Type	Imperial
Weight	62.000 lb
UPC Code	053893778761
Dimension B	6-1/4 in
Dimension H	11 in
Dimension H <sub>1</sub>	9-1/16 in
Dimension H <sub>2</sub>	4.46 in
Dimension d <sub>1</sub>	6-1/16 in
Dimension A	3-1/8 in
Dimension A <sub>1</sub>	3-1/8 in
Housing Width	4-1/2 in
Dimension L	11 in
Dimension L <sub>1</sub>	10-1/2 in
Dimension L <sub>2</sub>	5.96 in
e	0.49
X (if $F_a/F_r \leq e$ )	0.87
Y (if $F_a/F_r \leq e$ )	1.77
X (if $F_a/F_r > e$ )	0.7
Y (if $F_a/F_r > e$ )	2.14
K Factor	1.23
C <sub>90</sub> Dynamic Load Rating <sup>1</sup>	26900 lb
C <sub>0</sub> Static Load Rating	154000 lb



## NACHI BEARINGS OF AMERICA CORP.

$F_{a-max}$ Maximum Permissible Thrust Load <sup>2</sup>	6908 lb
$F_{r-max}$ Maximum Allowable Slip Fit Radial Load <sup>3</sup>	22000 lb
Max. Speed <sup>4</sup>	1530 rpm
Note	Note: All units have a 1/8 pipe thread grease fitting The Maximum Permissible Thrust Load applies to conditions of slip fit with set screw mounting or in applications where a large moment loading occur